

sako

TECHNICAL SPECIFICATION SAKO 85 FINNLIGHT

WEAPON	SAKO 85	
MODEL	FINNLIGHT	
MANUFACTURER	SAKO Ltd., FINLAND	
AVAILABLE ACTION SIZES	Right hand / S, SM, M, L	
OPERATION	Sako 85 manually operated bolt action	
BOLT	3 locking lugs, control round feed, mechanical ejection	
ACTION SIZE / CALIBER / RATE OF TWIST	S / 22-250 Rem / 14" S / 243 Win / 10" S / 260 Rem / 8" S / 7mm-08 Rem / 9.5" S / 308 Win / 11" SM / 270 Win Short Mag / 10" SM / 300 Win Short Mag / 11"	M / 25-06 Rem / 10" M / 6.5x55 SE / 8" M / 270 Win / 10" M / 30-06 Spr / 11" L / 7mm Rem Mag / 9.5" L / 300 Win Mag 11"
OVERALL WEIGHT w/o ACCESSORIES	S / 2.8 kg (6.8 lbs) SM, M / 2.9 kg (6.4 lbs)	L / 3.1 kg (6.8 lbs)
OVERALL LENGTH	S / 1030 mm (40.55") SM / 1125 mm (44.29")	M / 1085 mm (42.71") L / 1145 mm (45.07")
BARREL LENGTH	S / 515 mm (20.27") M / 570 mm (22.44")	SM, L / 620 mm (24.40")
LENGTH OF PULL	S / SM / M / L 355mm (14")	
BARREL	Fluted light hunting contour barrel (cold hammer forged)	
MAGAZINE	Detachable two row staggered steel magazine	
MAGAZINE CAPACITY	S / M 6 rounds (5 in magazine, 1 in chamber) SM / L 5 rounds (4 in magazine, 1 in chamber)	
SIGHTS	no iron sights	
OPTICAL SIGHT ATTACHEMENT	Sako 85 Conical dovetail rail	
METAL PARTS SURFACE FINISHING	Stainless steel barreled action and aluminum trigger guard + magazine plate	
STOCK	Synthetic stock with soft touch surface	
TRIGGER MECHANISM	Single stage trigger, pull adjustable 1-2kg (2-4 lbs), optional set trigger	
SAFETY	Two way safety with bolt realease lever	
ACCESSORIES	T25 torx key Cocking wrench Manual	

