## TECHNICAL SPECIFICATION SAKO 85 HUNTER

WEAPON	SAKO 85	
MODEL	HUNTER	
MANUFACTURER	SAKO Ltd., FINLAND	
AVAILABLE ACTION SIZES	Right hand / XS, S, SM, M, L	
	Left Hand / S, M, L	
OPERATION	Sako 85 manually operated bolt action	
BOLT	3 locking lugs, control round feed, mechanical ejection	
ACTION SIZE / CALIBER / RATE OF TWIST	XS / 204 Ruger / 12"	M / 25-06 Rem / 10"
	XS / 222 Rem / 14"	M / 6.5x55 SE / 8"
	XS / 223 Rem / 8", 12"	M / 270 Win / 10"
	S / 22-250 Rem / 14"	M / 7x64 / 10"
	S / 243 Win / 10"	M / 30-06 Spr / 11"
	S / 260 Rem / 8"	M / 8x57IS / 9.5"
	S / 7mm-08 Rem / 9.5"	M / 9.3x62 / 14"
	S / 308 Win / 11"	M / 9.3x66 (.370 Sako Mag) / 14"
	SM / 270 Win Short Mag / 10"	L / 7mm Rem Mag / 9.5"
	SM / 300 Win Short Mag / 11"	L / 300 Win Mag 11"
		L / 338 Win Mag / 10"
		L / .375 H&H / 12"
OVERALL WEIGHT w/o ACCESSORIES	XS / 2.9 kg (6 3/8 lbs)	SM, M / 3.3 kg (7 1/4 lbs)
	XS MT / 2.8 kg (6 3/16 lbs)	M MT / 3.2 kg (7 lbs)
	S / 3.2 kg (7 lbs)	L / 3.5 kg (7 3/4 lbs)
	S MT / 3.1 kg (6 7/8 lbs)	
OVERALL LENGTH	XS / 1065 mm (41 15/16")	SM / 1125 mm (44 5/16")
	XS MT / 1005 mm (39 9/16")	M / 1085 mm (42 3/4")
	S / 1075 mm (42 5/16")	M MT / 1025 (40 3/8")
	S MT / 1015 mm (40")	L / 1145 mm (45 1/16")
BARREL LENGTH	XS, S, M / 570 mm (22 7/16")	SM, L / 620 mm (24 3/8")
	XS, S, M MT / 510 mm (20")	
LENGTH OF PULL	XS / S / SM / M / L 355mm (14")	
BARREL	Light hunting contour barrel (cold hammer forged) optional muzzle thread	
	(338 Fed, 338 WM, 375 H&H, 8x57IS, 93x62, 93x66 with M15x1	
	other calibers M14x1 thread)	
MAGAZINE	Detachable two row staggered steel magazine	
MAGAZINE CAPACITY	XS 7 rounds (6 in magazine, 1 in chamber)	
	S / M 6 rounds (5 in magazine, 1 in chamber)	
	SM / L 5 rounds (4 in magazine, 1 in chamber)	
SIGHTS	Optional adjustable iron sights	
OPTICAL SIGHT ATTACHEMENT	Sako 85 tapered dovetail rail	
METAL PARTS SURFACE FINISHING	Matte blued metal parts	
STOCK	Monte Carlo style matte oil walnut stock with palm swell	
TRIGGER MECHANISM	Trigger pull adjustable 1 to 2kg (2 to 4 lbs) (Single set trigger optional)	
SAFETY	Two position safety with bolt realease lever	
ACCESSORIES	T25 torx key	
	Two sling swivels	
	Cocking wrench	
	Manual	

