

sako

TECHNICAL SPECIFICATION SAKO 85 SYNTHETIC STAINLESS

WEAPON	SAKO 85	
MODEL	SYNTHETIC STAINLESS	
MANUFACTURER	SAKO Ltd., FINLAND	
AVAILABLE ACTION SIZES	Right hand / S, SM, M, L	
OPERATION	Sako 85 manually operated bolt action	
BOLT	3 locking lugs, control round feed, mechanical ejection	
ACTION SIZE / CALIBER / RATE OF TWIST	S / 22-250 Rem / 14" S / 243 Win / 10" S / 260 Rem / 8" S / 7mm-08 Rem / 9.5" S / 308 Win / 11" SM / 270 Win Short Mag / 10" SM / 300 Win Short Mag / 11"	M / 25-06 Rem / 10" M / 6.5x55 SE / 8" M / 270 Win / 10" M / 30-06 Spr / 11" M / 8x57IS / 9.5" M / 9.3x62 / 14" M / 9.3x66 (.370 Sako Mag) / 14" L / 7mm Rem Mag / 9.5" L / 300 Win Mag 11" L / 338 Win Mag 10" L / 375 H&H Mag 12"
OVERALL WEIGHT w/o ACCESSORIES	S / 2.9 kg (6 3/8 lbs) S MT / 2.8 kg (6 3/16 lbs) SM, M / 3.0 kg (6 5/8 lbs)	M MT / 2.9 kg (6 3/8 lbs) L / 3.2 kg (7 lbs)
OVERALL LENGTH	S / 1075 mm (42 5/16") S MT / 1015 mm (40") SM / 1125 mm (44 5/16")	M / 1085 mm (42 3/4") M MT / 1025 (40 3/8") L / 1145 mm (45 1/16")
BARREL LENGTH	S, M / 570 mm (22 7/16") S, M MT / 510 mm (20")	SM, L / 620 mm (24 3/8")
LENGTH OF PULL	S / SM / M / L 355mm (14")	
BARREL	Light hunting contour barrel (cold hammer forged) optional muzzle thread (338 Fed, 8x57IS, 93x62, 93x66 with M15x1 other calibers M14x1 thread)	
MAGAZINE	Detachable two row staggered steel magazine	
MAGAZINE CAPACITY	S / M 6 rounds (5 in magazine, 1 in chamber) SM / L 5 rounds (4 in magazine, 1 in chamber)	
SIGHTS	Optional adjustable iron sights	
OPTICAL SIGHT ATTACHEMENT	Sako 85 Conical dovetail rail	
METAL PARTS SURFACE FINISHING	Stainless steel metal parts	
STOCK	Synthetic stock with soft touch surface	
TRIGGER MECHANISM	Trigger pull adjustable 1 to 2kg (2 to 4 lbs) (Single set trigger optional)	
SAFETY	Two way safety with bolt release lever	
ACCESSORIES	T25 torx key Cocking wrench Manual	



SAKO LTD., P.O.BOX 149, 11101 RIIHIMÄKI, FINLAND,
Telephone +358 10 8305200, Telefax +358 10 8305381 www.sako.fi