

TECHNICAL SPECIFICATION SAKO 85 LONG RANGE

| WEAPON | SAKO 85 |
|---------------------------------------|-------------------------------------------------------------------------|
| MODEL | LONG RANGE |
| MANUFACTURER | SAKO Ltd., FINLAND |
| AVAILABLE ACTION SIZES | Right hand / L, XL |
| OPERATION | Sako 85 manually operated bolt action |
| BOLT | 3 locking lugs, control round feed, mechanical ejection |
| ACTION SIZE / CALIBER / RATE OF TWIST | L / 300 Win Mag / 11" |
| | XL / 338 Lapua Mag / 10" |
| OVERALL WEIGHT w/o ACCESSORIES | L / 4.4 Kg (9.7 lbs) |
| | XL / 4.4 Kg (9.7 lbs) |
| OVERALL LENGTH | L / 1250mm (49.2") |
| | XL / 1250mm (49.2") |
| BARREL LENGTH | L, XL / 660 mm (26") |
| LENGTH OF PULL | L, XL / 355mm (14") |
| BARREL | Heavy contour barrel (cold hammer forged) |
| | muzzle break included with M16x1 thread |
| | Loctite 221 has been applied to muzzle break threads (easy dissasembly) |
| MAGAZINE | L / Fixed magazine with hinged floorplate |
| | XL / Fixed magazine with hinged floorplate |
| MAGAZINE CAPACITY | L / XL 5 rounds (4 in magazine, 1 in chamber) |
| SIGHTS | no open sights |
| OPTICAL SIGHT ATTACHEMENT | Sako 85 tapered dovetail rail |
| METAL PARTS SURFACE FINISHING | Matte blued |
| STOCK | Matte oiled dark grey / black laminated stock, palm swell |
| | double front swivel studs |
| TRIGGER MECHANISM | Single stage trigger adjustable 1 to 2kg (2 to 4 lbs) |
| SAFETY | Two position safety with bolt realease lever |
| ACCESSORIES | T25 torx key |
| | Two sling swivels |
| | Cocking wrench |
| | Manual |

