

TECHNICAL SPECIFICATION SAKO QUAD SYNTHETIC

WEAPON	SAKO QUAD
MODEL	SYNTHETIC
MANUFACTURER	SAKO Ltd., FINLAND
AVAILABLE ACTION SIZES	Right hand / STD
	Left Hand / -
OPERATION	Manually operated bolt action
BOLT	2 locking lugs, bolt lift angle 50°, spring ejection
CALIBER / RATE OF TWIST	22 LR / 16.5"
	22 WMRF / 16"
	17 HMR / 9"
	17 Mach 2 / 9"
OVERALL WEIGHT w/o ACCESSORIES	2.6 kg (5 3/4 lbs)
OVERALL LENGTH	1010 mm (39 3/4")
BARREL LENGTH	560 mm (22")
LENGTH OF PULL	340mm (13 3/8")
BARREL	Free floating hunting contour barrel (cold hammer forged)
	Optional thread 1/2"-20 UNF
MAGAZINE	Single row metal magazine, color coded for each caliber
MAGAZINE CAPACITY	5 round magazine
	Optional 10 round magazine (9 round for cal. 17 HMR and 22 WMR)
SIGHTS	No open sights, Optional iron sights are available
OPTICAL SIGHT ATTACHEMENT	11mm integral dovetail
METAL PARTS SURFACE FINISHING	Blued metal parts
STOCK	Black synthetic stock, length adjustable with spacers
TRIGGER MECHANISM	Single stage trigger adjustable 1 to 2kg (2 to 4 lbs) (Optional set trigger)
SAFETY	Two stage safety
ACCESSORIES	Manual

