

TECHNICAL SPECIFICATION SAKO A7 SYNTHETIC

WEAPON	SAKO A7	
MODEL	SYNTHETIC	
MANUFACTURER	SAKO Ltd., FINLAND	
AVAILABLE ACTION SIZES	Right hand / S, M	
OPERATION	Sako A7 manually operated bolt action	
BOLT	3 locking lugs, plunger ejection	
ACTION SIZE / CALIBER / RATE OF TWIST	S / 22-250 Rem / 14"	M / 25-06 Rem / 10"
	S / 243 Win / 10"	M / 270 Win / 10"
	S / 7mm-08 Rem / 9.5"	M / 30-06 Spr / 11"
	S / 308 Win / 11"	M / 7mm Rem Mag / 9.5"
	S / 270 Win Short Mag / 10"	M / 300 Win Mag 11"
	S / 300 Win Short Mag / 11"	
OVERALL WEIGHT w/o ACCESSORIES	S, M / 2.9 kg (6 3/8 lbs)	S, M Mag / 3.0 kg (6 5/8 lbs)
OVERALL LENGTH	S / 1075 mm (42 5/16")	M / 1085 mm (42 3/4")
	S MT / 1069 mm (42 5/64")	M MT / 1025 (40 3/8")
	S Mag / 1125 mm (44 5/16")	M Mag / 1135 mm (44 11/16")
	S Mag MT / 1070 mm (42 1/8")	M Mag MT / 1095 mm (43 7/64")
BARREL LENGTH	S, M / 570 mm (22 7/16")	S Mag MT / 565 mm (22 1/4")
	S, M Mag / 620 mm (24 3/8")	M Mag MT / 580 mm (22 27/32")
	S, M MT / 510 mm (20")	
LENGTH OF PULL	S / M 355mm (14")	
BARREL	Light hunting contour barrel (cold hammer forged) Optional muzzle thread(MT)	
MAGAZINE	Detachable single row synthetic magazine	
MAGAZINE CAPACITY	S / M 4 rounds (3 in magazine, 1 in chamber)	
SIGHTS	No open / optical sights	
OPTICAL SIGHT ATTACHEMENT	Weaver bases that are attached A-bolt style	
METAL PARTS SURFACE FINISHING	Blued metal parts	
STOCK	Synthetic stock with soft touch surface	
TRIGGER MECHANISM	Single stage trigger, pull adjustable 1 to 2kg (2 to 4 lbs)	
SAFETY	Two way safety with bolt realease lever	
ACCESSORIES	T25 torx key	
	Manual	

