

SAKO SPECIFICATION SAKO

SAKO A7 SYNTHETIC STAINLESS



SAKO A7 SYNTHETIC STAINLESS has a series of actions which are designated: Short action (S) incl. Short Magnum and Medium action (M) incl. Magnums. All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The BOLT features springloaded plunger ejection.

The single-column detachable MAGAZINE holds 3 rounds and can be loaded from the top. Magazine lips are made of stainless steel. Magazine release is prevented against accidental release (Pat. pend.).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The STOCK is made of glass-fiber reinforced copolymer polypropylene covered with Soft Touch surface and has a buttplate system where the length of pull is adjustable by means of spacers. Straight classic stock fits ambidextrous shooters.

SAKO A7 SYNTHETIC STAINLESS is available without open sights. Round top receiver is tapped to receive standard (Weaver) scope mount bases.

The totally free-floating BARREL is cold hammer-forged of stainless steel.

All models available also with short barrel with thread (calibers 270WSM, 300WSM, 7MMRM and 300WIN M15x1, other calibers M14x1) at the muzzle for muzzle brake or suppressor assembling.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
S	22-250 Rem	14"	S 1075 mm (42 5/16")
	243 Win	10"	S MT 1069 mm (42 5/64")
	7mm-08 Rem	9.5"	S Mag 1125 mm (44 5/16")
	308 Win	11"	S Mag MT 1070 mm (42 1/8")
	338 Federal	10"	M 1085 mm (42 3/4")
	270 Win Short Mag	10"	M MT 1025 mm (40 23/64")
	300 Win Short Mag	11"	M Mag 1135 mm (44 11/16")
M	25-06 Rem	10"	M Mag MT 1095 mm (43 7/64")
	270 Win	10"	Barrel length
	30-06 Sprg	11"	S / M 570 mm (22 7/16")
	7mm Rem Mag	9.5"	S / M Mag 620 mm (24 3/8")
	300 Win Mag	11"	S / M MT 510 mm (20")
			S Mag MT 565 mm (22 1/4")
			M Mag MT 580 mm (22 27/32")
			Weight
			S / M 2.9 kg (6 3/8 lbs)
			S / M Mag 3.0 kg (6 5/8 lbs)
			Length of pull
			S / M 355 mm (14")
			Cartridge capacity
			S / M 4 rounds (1 in chamber, 3 in magazine)