

# sako SPECIFICATION sako

## SAKO FINNFIRE HUNTER



SAKO FINNFIRE HUNTER rimfire rifle based on P94S action.

The ACTION is a bolt action design with two locking lugs, bolt lift angle 50°, bolt throw 30 mm (1.20 in) and firing pin travel 5 mm (0.20 in). Ejection is carried out with special spring.

The MAGAZINE is 5-shot clip magazine in cal 22 LR. 10-shot clip magazine is also available.

The TRIGGER is the same single-stage trigger as on other Sako-rifles. Adjustable from 1 to 2 kg (2 - 4 lbs). Also available with single set trigger mechanism as option.

Sliding SAFETY catch, located rear from the bolt handle, locks the trigger and the bolt.

The Sako 75 style walnut STOCK is oilfinished as standard. Mattlacquered stocks are also available.

Same OPEN SIGHTS with post bead with windage adjustment as on other Sako rifles.

Available also without open sights. 11 mm integral dovetail for scope mounting.

The free-floating BARREL is formed by the cold-hammering process. Thread 1/2"-20 UNF at the muzzle for silencer mounting.

### TECHNICAL DATA

#### Caliber and rate of twist

22 LR      420 mm      16.5"

#### Weight

P94S      2.6 kg      5 3/4 lbs

#### Overall length

P94S      1000 mm      39 1/2"

#### Barrel length

P94S      560 mm      22"