



SPECIFICATION

TIKKA T3 VARMINT



TIKKA T3 VARMINT based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 5-6 cartridges. Single-column 3-4-shot (depending on caliber) magazine is available as accessory (in Short Mag calibers as standard).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Cheek piece and extra-wide forend carried out with add-ons. Straight stock features ambidextrous palm swell.

TIKKA T3 VARMINT is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The heavy, free-floating BARREL is cold hammer-forged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
	222 Rem	14"	T3	1110 mm (43 3/4")
	223 Rem	8"	Barrel length	
	22-250 Rem	14"	T3	600 mm (23 3/4")
	243 Win	10"	Weight	
	7mm-08 Rem	9.5"	T3	3.6 kg (8 lbs)
	308 Win	11"	Cartridge capacity	
	T3	25-06 Rem	10"	T3 222 Rem, 223 Rem 7 rounds (1 in chamber, 6 in clip magazine)
	6.5x55 SE	8"	T3 270 Win Short Mag, 300 Win Short Mag 4 rounds (1 in chamber, 3 in clip magazine)	
	270 Win	10"	T3 other calibers 6 rounds (1 in chamber, 5 in clip magazine)	
	30-06 Sprg	11"		
	9.3x62	14"		
	7 mm Rem Mag	9.5"		
	300 Win Mag	11"		
	338 Win Mag	10"		
	270 Win Short Mag	10"		
300 Win Short Mag	11"			