



SPECIFICATION

TIKKA T3 BATTUE



TIKKA T3 BATTUE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3 cartridges. Single-column 5-shot magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The walnut STOCK is oilfinished as standard and has a buttplate system where the length of pull is adjustable by means of spacers. Matte-lacquered stocks are also available. Straight stock features ambidextrous palm swell.

Special OPEN SIGHTS designed for snapshooting have adjustable rear sight (elevation). Rear sight leaf, bead and rear sight rib are also provided with illuminated dots. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The short, free-floating BARREL is cold hammer-forged.

TECHNICAL DATA

| Action | caliber | rate of twist | Overall length | |
|--------|-------------------|---------------|---|----------------------|
| T3 | 308 Win | 11" | T3 | 1010 mm (39 3/4") |
| | 7x64 | 10" | Barrel length | |
| | 30-06 Sprg | 11" | T3 | 500 mm (19 11/16") |
| | 9.3x62 | 14" | Weight | |
| | 300 Win Mag | 11" | T3 | 3.1 kg (6 13/16 lbs) |
| | 300 Win Short Mag | 11" | Cartridge capacity | |
| | | | T3 all calibers 4 rounds (1 in chamber, 3 in clip magazine) | |