



SPECIFICATION

TIKKA T3 COMPACT



TIKKA T3 COMPACT based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3 cartridges. Single-column 5-shot magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The walnut STOCK is oilfinished and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell and shorter butt and fore-end.

TIKKA T3 COMPACT is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is adjustable sideways and front sight in elevation. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The short, free-floating BARREL is cold hammer-forged. Available also with M14x1 thread at the muzzle for muzzle brake or suppressor assembling.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	243 Win	10"	T3	1000 mm (39 3/8")
	260 Rem	8"	Barrel length	
	7mm-08 Rem	9.5"	T3	510 mm (20")
	308 Win	11"	Weight	
	25-06 Rem	10"	T3	3.0 kg (6 5/8 lbs)
			Length of pull	
			T3	335 mm (13 3/16")
			Cartridge capacity	
			T3	3 rounds (1 in chamber, 2 in clip magazine)