



SPECIFICATION

TIKKA T3 LITE STAINLESS



TIKKA T3 LITE STAINLESS based on a two locking lug T3 all-weather action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt and receiver are made of stainless steel.

The single-column detachable clip MAGAZINE holds 3-4 cartridges. Single-column 5-6-shot (depending on caliber) magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell.

TIKKA T3 LITE STAINLESS is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The free-floating, stainless steel BARREL is cold hammer-forged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	222 Rem	14"	T3	1080 mm (42 1/2")
	223 Rem	8"	T3 Mag	1130 mm (44 1/2")
	22-250 Rem	14"	Barrel length	
	243 Win	10"	T3	570 mm (22 7/16")
	7mm-08 Rem	9.5"	T3 Mag	620 mm (24 3/8")
	308 Win	11"	Weight	
	25-06 Rem	10"	T3	2.8 kg (6 3/16 lbs)
	6.5x55 SE	8"	T3 Mag	2.9 kg (6 3/8 lbs)
	270 Win	10"	Cartridge capacity	
	30-06 Sprg	11"	T3 222 Rem, 223 Rem	5 rounds (1 in chamber, 4 in clip magazine)
	9.3x62	14"	T3 other calibers	4 rounds (1 in chamber, 3 in clip magazine)
	7 mm Rem Mag	9.5"		
	300 Win Mag	11"		
	338 Win Mag	10"		
	270 Win Short Mag	10"		
	300 Win Short Mag	11"		