



# SPECIFICATION

## TIKKA T3 LITE



TIKKA T3 LITE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3-4 cartridges. Single-column 5-6-shot (depending on caliber) magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell.

TIKKA T3 LITE is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is sideways adjustable. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The free-floating BARREL is cold hammer-forged.

### TECHNICAL DATA

Action	caliber	rate of twist	Overall length
T3	222 Rem	14"	T3 1080 mm (42 1/2")
	223 Rem	8"	T3 Mag 1130 mm (44 1/2")
	22-250 Rem	14"	<b>Barrel length</b>
	243 Win	10"	T3 570 mm (22 7/16")
	7mm-08 Rem	9.5"	T3 Mag 620 mm (24 3/8")
	308 Win	11"	<b>Weight</b>
	25-06 Rem	10"	T3 2.8 kg (6 3/16 lbs)
	6.5x55 SE	8"	T3 Mag 2.9 kg (6 3/8 lbs)
	270 Win	10"	<b>Cartridge capacity</b>
	7x64	10"	T3 222 Rem, 223 Rem 5 rounds (1 in chamber, 4 in clip magazine)
	30-06 Sprg	11"	T3 other calibers 4 rounds (1 in chamber, 3 in clip magazine)
	9.3x62	14"	
	7 mm Rem Mag	9.5"	
	300 Win Mag	11"	
	338 Win Mag	10"	
	270 Win Short Mag	10"	
	300 Win Short Mag	11"	