

SPECIFICATION



TIKKA T3 LITE ADJUSTABLE



TIKKA T3 LITE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3-4 cartridges. Single-column 5-6-shot (depending on caliber) magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell. TIKKA T3 LITE is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is sideways adjustable. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases. The free-floating BARREL is cold hammer-forged.

The perfect choice for hunters who want to be able to adjust the cheek piece and length of pull, especially in low-light conditions. The built-in option of being able to raise the cheekpiece optimizes optics.

TECHNICAL DATA

Action	caliber rate 204 Ruger 222 Rem 223 Rem	e of twist 12" 14" 8,12"	Overall length T3 T3 Mag	1080 mm (42 1/2") 1130 mm (44 1/2")
To	22-250 Rem 243 Win 260 Rem 7mm-08 Rem 308 Win	14" 10" 8" 9,5" 11"	T3 Mag Weight	570 mm (22 7/16") 620 mm (24 3/8") 2.8 kg (6 3/16 lbs)
Т3	25-06 Rem 6,5x55 SE 270 Win 7x64 30-06 Sprg 8x57IS 9,3x62 7mm Rem Mag 300 Win Mag 338 Win Mag 270 Win Short Mag 300 Win Short Mag		T3 Mag Cartridge capacity T3 204 Ruger, 222 Rem, (1 in chamber, 4 in clip m T3 other calibers 4 Roun in clip magazine)	2.9 kg (6 3/8 lbs) 223 Rem 5 Rounds nagazine)