

sako

TECHNICAL SPECIFICATION TIKKA T3 CTR **NEW 2014**

| | |
|---|---|
| WEAPON | TIKKA T3 |
| MODEL | CTR |
| MANUFACTURER | SAKO Ltd., FINLAND |
| AVAILABLE ACTION SIZES | Right hand / STD |
| OPERATION | Tikka T3 manually operated bolt action |
| BOLT | 2 locking lugs, plunger ejection, teflon coated, synthetic larger bolt knob |
| CALIBER / RATE OF TWIST / MAGAZINE CAPACITY | 308 Win / 11" / (10 in magazine, 1 in chamber) 260 Rem / 8" / (10 in magazine, 1 in chamber) |
| OVERALL WEIGHT w/o ACCESSORIES | 3.4 Kg (7.5 lbs) |
| OVERALL LENGTH | 1020 mm (40 3/16") |
| BARREL LENGTH | 510 mm (20") |
| LENGTH OF PULL | Minimum 335mm (13.2") adjustable with spacers (two 4mm spacers included) |
| BARREL | Mid contour barrel (cold hammer forged) with 5/8x24 muzzle thread |
| MAGAZINE | Detachable staggered two row steel magazine |
| SIGHTS | No open sights |
| OPTICAL SIGHT ATTACHMENT | Picatinny rail |
| METAL PARTS SURFACE FINISHING | Blued finish / anodized aluminium trigger guard |
| STOCK | Black synthetic stock with cheek piece |
| TRIGGER MECHANISM | Single stage trigger, adjustable pull 1 to 2kg (2 to 4 lbs) |
| SAFETY | Two position safety |
| ACCESSORIES | Manual |

